

SuperFlex Universal:

Hot rod & Kit car products

SF1276 Range

The SF1276 is of tried and trusted TVR Chimera & Griffith wishbone origin. It has in the past, and still is being applied to kit car manufacture. This is our medium sized option, and proven capable of offering performance & durability when fitted to powerful V8 & V10 engined sports cars

An assembly lubricant sachet is included: One for every eight assemblies.

Part Ref	Description	Notes
SF1276P-90	Polyurethane 25.45mm OD (Nom. 1") 90 shore Top Hat Bush Only	Flange is 3.9mm thick x 32.5mm OD
SF1276P-95	Polyurethane 25.45mm OD (Nom. 1") 95 shore Top Hat Bush Only, Hard race option	Flange is 3.9mm thick x 32.5mm OD
SF1276T	Crush tube, stainless steel	16mm x 7/16" (11.11mm) ID x 50.5mm long
SF1276-90	Assembly; 2 90 shore PU Top hat bushes & stainless steel tube	
SF1276-95	Assembly; 2 95 shore PU Top hat bushes & stainless steel tube, Hard race option	
SF1276S	Housing/shell (Weld on) for car builders, in DIN 2393 cold drawn seamless tube 4.06mm wall thickness	Nominal size 31.75mm OD x 25.25mm ID x 42.7mm long